North America's Leader in Hazardous Material Information Management

1905 Aston Avenue, Carlsbad, CA 92008 Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 10/07/2005

To: MSDS Requester

From: 3E Company

Subject: The MSDS you have requested

[] MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communicatin Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

[X] MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

[] MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

[] MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: American Home Products Corp.

Product Name: Plastic Wood Cellulose Fiber Filler, Natural (Cans & Tubes) (DISCONTINUED)

Page 1 of 2 issue Date: 9-30-92

MATERIAL SAFETY DATA SHEET

Reckitt & Colman Inc.

P. O. Box 943

Wayne, NJ 07474-0943

800-338-6167 for medical emergency 800-424-9300 for transportation emergency 201-633-6700 for technical information during business hours NFPA Hazard Rating: 0 Health Flammability 3 n Reactivity

SECTION 1 MATERIAL IDENTIFICATION

Name: Plastic Wood Cellulose Fiber Filler (natural and assorted colors)

SECTION 2 INGREDIENT INFORMATION

Chemical/Common Name	CAS No.	% by Weight	Exposure Limits OSHA TWA	ACGIH TWA
Acetone	67-64-1	20-30	750 ppm TWA 1000 ppm STEL	750 ppm TWA 1000 ppm STEL
n-Butyl Acetate	123-86-4	1-10	150 pppm TWA 200 ppm STEL	150 ppm TWA 200 ppm STEL
Calcium carbonate	1317-65-3	30-40	15 mg/m³ TWA 5 mg/m³ respirable fraction	10 mg³ TWA

SECTION 3 HAZARDS IDENTIFICATION

Signs and Symptoms of Overexposure: Irritating if in eyes.

Potential Health Effects

Eve Contact: Eye irritant

Skin Contact: Not a primary skin irritant.

Ingestion: Not orally toxic.

Inhalation: Inhalation toxicity not determined.

Chronic Effects: The product has not been tested as a whole for chronic effects. No ingredient is a

listed carcinogen (NTP, IARC, OSHA).

Medical Conditions Recognized as Being Aggravated by Exposure to the Product: None known

SECTION 4 FIRST AID MEASURES

Eye Contact: Flush with water. Call physician or Poison Control Center.

There is no specific antidote. Skin Contact:)

Treatment of overexposure should be directed at the Ingestion:)

control of symptoms and the clinical condition. Inhalation:

Name: Plastic Wood Cellulose Fiber Filler (natural and assorted colors) Page 2 of 2 Issue Date: 9-30-92

SECTION 5 FIRE FIGHTING MEASURES

Flammability Properties

Flash Point: 21 - 25 °F (Penske-Martens Closed Cup)

Extinguishing Media: Water, CO2, dry chemical

Fire Fighting Instructions: Wear full protective equipment: eye/face (shield), body (full bunker gear), respiratory

(SCBA).

SECTION 6 ACCIDENTAL RELEASE MEASURES

In Case of Leakage or Spillage: Pick up immediately and place in closed fireproof container.

SECTION 7 HANDLING AND STORAGE

Extremely flammable mixture. Do not use or store near fire or flame. Do not smoke while using. Keep out of reach of children.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Requirements: No specific controls are needed.

Personal Protective Equipment: None required

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Paste with characteristic color

Odor: Strong organic solvent pH: Not applicable

Boiling Point: Not applicable Melting Point: Not applicable

Freezing Point: Not determined Specific Gravity: 1.4

Solubility in Water: Insoluble Vapor Pressure: Not determined Volatiles: Approx. 40% Pressure in Can: Not applicable

Vapor Density (Air = 1): Not determined

SECTION 10 STABILITY AND REACTIVITY

Storage Stability: X Stable	Unstable Co			
Hazardous Polymerization:	May occur X V	Will not occur	Conditions to Avoid:	None known
Incompatibility (Materials to avoid)	None known			

Hazardous Decomposition Products: Combustion products of wood

SECTION 11 DISPOSAL

Consumer disposal: Wrap container and put in trash collection.

Large quantity disposal: If paste, transport to secure landfill, approved incinerator, or other facility in accord with

federal, state, and local law. If solid, discard with trash collection.

SECTION 12 ADDITIONAL COMMENTS

CERCLA ("Superfund") Reportable Quantity: 17,400 pounds (Acetone) (only if in paste state)

SARA Section 313 Chemicals: Acetone, di-n-octyl phthalate

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.